

AL-A28



Key Specifications/Special Features:

1. Synthesized or Crystal Type
2. Loud Buzzer, Strong Vibrator
3. Blue Back-light, Large Display
4. 6 Keys Operation, User Friendly Interface
5. Selective PC or Hand Programmable
6. IP53 Approval for Water-resistance and Dust-tight
7. AAA Rechargeable Battery
8. Quick charging
9. Charger with relay output is optional
10. Support Languages: English, Spanish, Portuguese, Russian, German, and French

AL-A28 Rich Sophistication:

- * 4 Lines, Total 84 Alphanumeric One Page Display
- * IP-53 Approval
- * Blue Back-Light, Large Screen
- * 6 Keys Operation, Easy Operation
- * Use Rechargeable or Alkaline Battery: AAA Size
- * Desk Charger (Optional)
- * Large Memory Size; Total Capacity 259,062 Letters
- * General Message: 16 sets + Message Full:10 sets, total capacity 20480 letters
- * Personal Message: 10 sets, total capacity 1000 letters
- * Mail Drop: 15 sets, total capacity 228,345 letters
- * 4 Beep Alerts with LED Flash, 10 Melody Alerts with LED Flash, Vibration with LED Flash, LED Flash Only, or Sleep
- * 12hr or 24 hr format real time clock (selectable)
- * Unread Message Reminder Alert
- * Error Message, Duplicate Message, Full Message Indicator
- * Manual pager on/off
- * Convenient Functions; 5 Daily Alarm, Auto Scroll, Auto Sleep, Zoom In/Out
- * 10 Sets for Messages Lock
- * Real Time Clock Calendar
- * Message Time Stamp
- * Month, Date, Year, Time Display (British or American date format)
- * 5 sets daily alarm
- * Memory retention during battery replacement
- * Page scrolling (selectable)
- * Selective PC or Hand Programming
- * Up to 8 Capcodes for POCASG

Specifications:

Model	AL-A28
Frequency	138~174MHz, 408~473MHz, 929~932MHz
Paging Sensitivity	5 uV per meter for 512 bps POCASG ; 7 uV per meter for 1200 bps POCASG
EIA Selectivity	60 dB \pm 25KHz
Spurious Rejection	55 dB below carrier
Image Rejection	50 dB below carrier
Frequency Stability	-10° to 50°C (+25°C ref.) 7 ppm for UHF, 10 ppm for VHF
Frequency Deviation	\pm 4.5 KHz
Code Format	31/21 POCASG code format (CCIR Code # 1)
Alert Tone Loudness	85db @ 10 cm
Transmission speed	512 bps / 1200 bps / 2400 bps
Dimension	80(L) x 53(W) x 20(H) mm
Weight with battery	Approximately 56.5 g (Without Battery)